



Office de la Propriété  
Intellectuelle  
du Canada  
Un organisme  
d'Industrie Canada

Canadian  
Intellectual Property  
Office  
An agency of  
Industry Canada

CA 2456056 A1 2003/02/13

(21) 2 456 056

(12) DEMANDE DE BREVET CANADIEN  
CANADIAN PATENT APPLICATION


(13) A1

(86) Date de dépôt PCT/PCT Filing Date: 2002/07/31  
(87) Date publication PCT/PCT Publication Date: 2003/02/13  
(85) Entrée phase nationale/National Entry: 2004/01/30  
(86) N° demande PCT/PCT Application No.: JP 2002/007779  
(87) N° publication PCT/PCT Publication No.: 2003/012899  
(30) Priorité/Priority: 2001/07/31 (2001-231538) JP

(51) Cl.Int.<sup>7</sup>/Int.Cl.<sup>7</sup> H01M 4/02, C01B 31/02, H01M 4/04,  
H01M 4/58, H01M 10/40  
(71) Demandeurs/Applicants:  
MITSUI ENGINEERING & SHIPBUILDING CO., LTD.,  
JP;  
OKADA, SHIGETO, JP;  
YAMAKI, JUN-ICHI, JP  
(72) Inventeurs/Inventors:  
HATTA, NAOKI, JP;  
OKADA, SHIGETO, JP;  
YAMAKI, JUN-ICHI, JP  
(74) Agent: KIRBY EADES GALE BAKER

(54) Titre : PROCEDE POUR PRODUIRE LE MATERIAU D'ANODE D'UN ACCUMULATEUR, ET ACCUMULATEUR  
AINSI CONSTITUE

(54) Title: METHOD OF PRODUCING SECONDARY BATTERY ANODE MATERIAL, AND SECONDARY BATTERY



(57) Abrégé/Abstract:

A method of producing a secondary battery anode material for producing an anode material by firing raw materials, characterized in that the raw materials are fired by being added with one kind or at least two kinds selected from a group consisting of hydrogen, water and vapor, and a conductive carbon and/or a substance capable of producing a conductive carbon by thermolysis. The secondary battery anode material obtained by this method facilitates the entry/exit of alkali metal

**(57) Abrégé(suite)/Abstract(continued):**

ions including lithium ions between the interiors of anode material grains and an electrolyte due to fine-grained crystals to restrict electrode reaction polarization, and increases a contact area between the anode material and a conductivity imparting material to improve conductivity and enhance a voltage efficiency and an effective battery capacity.